

Flow Boiling Critical heat Flux in Reduced Gravity

Issam Mudawar & Hui Zhang
**Boiling and Two-Phase Flow Laboratory
Purdue University**

and

Mohammad M. Hasan
NASA Glenn Research Center



June 23, 2004

**Conference on Strategic Research to Enable
NASA's Space Exploration Missions**

Prof. I. Mudawar

Rationale

- ➔ **Critical heat flux (CHF) is key design parameter for heat-flux-controlled devices**
- ➔ **Ability to predict CHF is of paramount importance to both safety and reliability of two-phase systems**
- ➔ **Vast majority of reduced-gravity boiling studies focused on pool rather than flow boiling**
- ➔ **There are conflicting recommendations concerning viability of pool boiling in microgravity**
- ➔ **Flow boiling is proven method for enhancing CHF relative to pool boiling**
- ➔ **Bulk motion increases CHF by flushing bubbles away from heated wall before they coalesce into insulating vapor blanket, and by constantly replenishing wall with bulk liquid**
- ➔ **Low pumping power favors reducing flow velocity**
- ➔ **Minimum velocity is therefore sought which can adequately increase CHF and suppress detrimental effects of reduced gravity**



June 23, 2004

**Conference on Strategic Research to Enable
NASA's Space Exploration Missions**

Prof. I. Mudawar

Significance

NASA/TM-2004-212940: Workshop on Critical Issues in Microgravity Fluids, Transport, and Reaction Processes in Advanced Human Support Technology

Focus Area: Thermal Systems and Phase Change Processes

- **Future missions for exploration of solar system will require enabling technologies for efficient and reliable energy generation** (nuclear, chemical, solar sources), **storage** (rechargeable batteries, regenerative fuel cells, flywheels, latent heat phase change), and **transfer** (cabin temperature control, space suit temperature regulation)
- **Need for improved energy-to-mass ratios suggests replacing present single-phase operations with two-phase systems.** Future design of important thermal subsystems in boilers, condensers, evaporators, heat exchangers, cryogenic fluid storage units, fuel cells, radiators and heat pipes **involve complex multiphase fluid flow and transport issues**
- **Full understanding of multiphase transport phenomena** associated with operation of thermal and phase change subsystems in microgravity needed for both design and safe and efficient operation in space




June 23, 2004

Conference on Strategic Research to Enable
NASA's Space Exploration Missions

Prof. I. Mudawar

Pertinent AHST System: Power Generation Cycles, high power-to-weight ratio Rankine cycle for long-duration missions



High Priority Recommendations:

- Attainment of phenomenological understanding and accumulation of empirical data for **two-phase flow** in micro- and macro-geometries, **boiling heat transfer**, and phase-distribution and phase-transition phenomena **in microgravity**
- Development of **empirical correlations, theoretical models and scaling laws** for **two-phase flow** in complicated geometries, **boiling and condensation heat transfer**, and phase-distribution and phase-transition phenomena in microgravity
- Development of **stability criteria** for two-phase heat transfer loops in microgravity
- Development of advanced, efficient, and reliable **vapor compression heat pump technology**

Challenge

Reduced gravity flow boiling heat transfer and critical heat flux data and models virtually nonexistent!!!



June 23, 2004


Conference on Strategic Research to Enable
NASA's Space Exploration Missions

Prof. I. Mudawar



Effects of Orientation on Pool Boiling CHF at One g_e

CHF from a horizontal surface


$1 g_e$



Heat Flux




Phase Change Photo Library (Mudawar, 1984 - 2004)




CHF = 26 W/cm²




Saturated PF-5052



CHF = 20 W/cm²



CHF = 5 W/cm²



Howard & Mudawar (1999)




June 23, 2004

Conference on Strategic Research to Enable NASA's Space Exploration Missions

Prof. I. Mudawar


Bubble Coalescence Effects

Incipient Flow Boiling



Pool Boiling


(50% CHF)



< 20% CHF

60% CHF

CHF



Flow
Boiling








June 23, 2004

Conference on Strategic Research to Enable
NASA's Space Exploration Missions

Prof. I. Mudawar

One-g_e Flow Boiling CHF Apparatus



June 23, 2004

Conference on Strategic Research to Enable
NASA's Space Exploration Missions


Prof. I. Mudawar

Vapor Behavior for Saturated Flow


Downward-facing
heater

Upward-facing
heater

Upflow



$U = 0.1 \text{ m/s}$



Downflow

$U = 1.5 \text{ m/s}$




June 23, 2004

Conference on Strategic Research to Enable
NASA's Space Exploration Missions

Prof. I. Mudawar

Variation of CHF with Orientation and Flow Velocity at $1 g_e$





June 23, 2004

Conference on Strategic Research to Enable
NASA's Space Exploration Missions

Prof. I. Mudawar

CHF Regime Map





Wavy Vapor Layer Regime

5.0 mm



$U = 1.5 \text{ m/s}$




Flow




June 23, 2004

Conference on Strategic Research to Enable
NASA's Space Exploration Missions

Prof. I. Mudawar

Vapor Momentum vs Interfacial Pressure



Interfacial Lift-off Model

- **Critical Wavelength:**

$$\frac{2\pi}{\lambda_c} = \frac{\rho_f \rho_g (U_g - U_f)^2}{2\sigma(\rho_f + \rho_g)} + \sqrt{\left[\frac{\rho_f \rho_g (U_g - U_f)^2}{2\sigma(\rho_f + \rho_g)} \right]^2 + \frac{(\rho_f - \rho_g)g \cos \theta}{\sigma}}$$

- **Interfacial Pressure Difference:**

$$\overline{P_f - P_g} = \frac{4\sigma b \sin(b\pi)}{b\lambda^2}$$

- **Interfacial Lift-Off Heat Flux:**

$$q_w'' = \rho_g (c_{p,f} \Delta T_{sub,i} + h_{fg}) \left(\frac{P_f - P_g}{\rho_g} \right)^{1/2}$$


- **Heater Energy Balance:**

$$q_m'' = b q_w''$$

- **Critical Heat Flux:**

$$q_m'' = \rho_g (c_{p,f} \Delta T_{sub,i} + h_{fg}) \left[\frac{4\sigma b \sin(b\pi)}{\rho_g} \right]^{1/2} \left(\frac{\rho}{\lambda_c} \right)^{1/2}$$

Comparison of Measured and Predicted CHF at 1 g_e



June 23, 2004

Conference on Strategic Research to Enable
NASA's Space Exploration Missions

Prof. I. Mudawar

Minimum Velocity Required to Overcome Body Force Effects

Negligible Component of Body Force Perpendicular to Wall

$$\frac{2\pi \sigma (\rho_f + \rho_g)}{\lambda_c \rho_f \rho_g (\Delta U)^2} = \frac{1}{2} \left\{ 1 + \sqrt{1 + 4 \frac{(\rho_f - \rho_g)(\rho_f + \rho_g)^2 \sigma g}{\rho_f^2 \rho_g^2 (\Delta U)^4}} \right\}$$


$$\frac{Bo}{We^2} = \frac{(\rho_f - \rho_g)(\rho_f + \rho_g)^2 \sigma g}{\rho_f^2 \rho_g^2 U^4} \leq 0.09$$

$$Bo = \frac{(\rho_f - \rho_g)gL^2}{\sigma} \quad We = \frac{\rho_f \rho_g U^2 L}{(\rho_f + \rho_g)\sigma}$$


Negligible Component of Body Force Parallel to Wall

$$U_\infty \sim \left[\frac{(\rho_f - \rho_g)gD_h}{\rho_f^{1/2}} \right]^{1/2} \ll U$$

$$\frac{1}{Fr} = \frac{(\rho_f - \rho_g)gD_h}{\rho_f U^2} \leq 0.13$$



Minimum Velocity Required to Overcome Body Force Effects



June 23, 2004


Conference on Strategic Research to Enable
NASA's Space Exploration Missions

Prof. I. Mudawar

Reduced Gravity Flow Boiling CHF Apparatus




Flight Rack



Light Source

Flow Boiling Module

Video Camera



Two-Phase Loop

Phase Change Photo Library (Mudawar, 1984 - 2004)



June 23, 2004

**Conference on Strategic Research to Enable
NASA's Space Exploration Missions**


Prof. I. Mudawar

KC-135 Microgravity Experiments

NASA Glenn Research Center, April 2004



Flight Trajectory



Operators:

- Dwayne Kiefer (QSS)
- Dr. Charles Niederhaus (NASA)
- Dr. Juan Agui (NASA)

Phase Change Photo Library
(Mudawar, 1984 - 2004)




June 23, 2004

Conference on Strategic Research to Enable
NASA's Space Exploration Missions

Prof. I. Mudawar

Reduced Gravity Flow Loop



June 23, 2004

Conference on Strategic Research to Enable
NASA's Space Exploration Missions

Prof. I. Mudawar

Reduced Gravity Flow Loop



Coolant Reservoir



Accumulator



Heat Exchanger




Flow Boiling Module



Pump



Filter



Turbine Flowmeter



In-Line Heater






June 23, 2004

Conference on Strategic Research to Enable
NASA's Space Exploration Missions

Prof. I. Mudawar

Flow Boiling Module




June 23, 2004

Conference on Strategic Research to Enable
NASA's Space Exploration Missions

Prof. I. Mudawar

Thermal Response of Heater




June 23, 2004

Conference on Strategic Research to Enable
NASA's Space Exploration Missions

Prof. I. Mudawar

Parabolic Flight Results

FC-72, $U = 0.14$ m/s



Phase Change Photo Library
(Mudawar, 1984 - 2004)




June 23, 2004

Conference on Strategic Research to Enable
NASA's Space Exploration Missions

Prof. I. Mudawar

Parabolic Flight Results

FC-72, $U = 1.40$ m/s



Phase Change Photo Library
(Mudawar, 1984 - 2004)




June 23, 2004

Conference on Strategic Research to Enable
NASA's Space Exploration Missions

Prof. I. Mudawar

Parabolic Flight Results



Phase Change Photo Library
(Mudawar, 1984 - 2004)



June 23, 2004

Conference on Strategic Research to Enable
NASA's Space Exploration Missions

Prof. I. Mudawar

One-G Flow Orientation Study

- ➔ At high velocities, CHF at all orientations dominated by **Wavy Vapor Layer Regime**. Vapor layer layer propagates along heated wall permitting liquid contact only in troughs of interfacial waves. CHF occurs when liquid contact regions are lifted from wall due to intense vapor effusion
- ➔ **Interfacial Lift-off Model** very effective at capturing overall dependence of CHF on orientation in **Wavy Vapor Layer Regime**
- ➔ **Flooding limit** better suited to CHF prediction in low velocity downflow orientations
- ➔ Dimensionless criteria developed for **minimum flow velocity** required to overcome body force effects on flow boiling CHF



Reduced Gravity Study

- ➔ **Body force has significant effect on nucleate flow boiling at low flow velocities**
- ➔ **Very low coolant velocities (especially below 0.5 m/s) greatly reduce CHF in microgravity**
- ➔ **Increasing flow velocity reduces CHF sensitivity to body force and can eliminate detrimental effects of microgravity on CHF**
- ➔ **Experimental CHF data corresponding to microgravity, lunar and Martian environments demonstrate existence of minimum velocity above which effects of body force on CHF are suppressed**
- ➔ **Experimental CHF data support predictions of theoretical dimensionless minimum velocity criteria**



Conclusions

Practical Implications

- **This study provides systematic method for reducing power consumption in reduced gravity systems by adopting minimum velocity required to provide adequate CHF and preclude detrimental effects of reduced gravity**
- **This study proves it is possible to use existing 1 g_e flow boiling and CHF correlations and models to design reduced gravity systems provided minimum velocity criteria are met**



June 23, 2004

**Conference on Strategic Research to Enable
NASA's Space Exploration Missions**

Prof. I. Mudawar